



## Product information

No. 11901000

# KAJO-2-Takt-Motorenöl

**KAJO-2-stroke engine oil** is made from high quality base oils. Ash free components guarantee perfect wear protection and avoid corrosion, deposits and glow ignitions even under high load.

**Practical advantages:**

**KAJO-2-stroke engine oil** is a self-mixing engine oil and suitable for lubricating air and water cooled 2-stroke engines (except for outboard motors).

**KAJO-2-stroke engine oil** meets with the requirements with regard to lubricating motors of

lawn mowers as well as chain saws. Besides, it is applied in motors with automatic fresh oil systems (autolube system).

**KAJO-2-stroke engine oil** meets with the requirements of:

- API TC (former API TSC 3)
- JASO FC
- Global GC/GD
- T.I.S.I.

**Typical characteristics:**

| Properties           | Value | Unit               | Standard         |
|----------------------|-------|--------------------|------------------|
| Density at 15°C      | 880   | kg/m <sup>3</sup>  | DIN EN ISO 12185 |
| Viscosity at 40°C    | 110   | mm <sup>2</sup> /s | DIN EN ISO 3104  |
| Viscosity at 100°C   | 12.5  | mm <sup>2</sup> /s | DIN EN ISO 3104  |
| Pourpoint            | -12   | °C                 | ASTM D97         |
| Flash point PM / COC | >150  | °C                 | DIN EN ISO 2592  |

Version 2

revised: 09.05.2016

DR/MJ/AO

All data are average values and subject to production related fluctuations.  
Still subject to change.

D-59609 Anröchte • Phone: +49 (0)2947 881-0 • FAX: +49 (0)2947 881-120  
email: [Schmierstoffe@KAJO.de](mailto:Schmierstoffe@KAJO.de) • Internet: [www.KAJO.de](http://www.KAJO.de)