

Product information 38700000

KAJO-Korrosionsschutzöl E

KAJO-Korrosionsschutzöl E is a mixture of selected mineral oil raffinates and corrosion protection additives. By using a non-ionic surfactant water can be emulsified without problems.

Practical advantages:

KAJO-Korrosionsschutzöl E is excellently suitable for the protection of corrosion-sensitive metal surfaces. Especially in cases where the metal is frequently exposed to condensation water, the application of **KAJO-Korrosionsschutzöl E** is indicated, water is emulsified without problems.

Due to the low base oil viscosity and high wetting ability **KAJO-Korrosionsschutzöl E** protects even at places difficult to access.

Properties

- very good corrosion protection
- good creep and wetting properties
- high water binding
- sprayable

Typical characteristics:

Typical characteristics.			
Properties	Value	Unit	Test method
Appearance, 20°C	light yellow, clear	-	-
Kin. viscosity at 40 °C	20	mm²/s	ASTM D 7042
Density at 20°C	860	kg/m³	DIN EN ISO 12 185
Flash point, base oil (COC)	200	°C	DIN EN ISO 2592
Anti-corrosion steel fingers, procedure B	pass		DIN ISO 7120

Version: V3 revised: 05.04.2022 Bac/TK/CF/DG/Pos Page 1 / 1 Date printed: 05.04.2022

All ratings are average values and are subject to production-related fluctuations. Changes may be reserved.

For the specified parameters, comparability and repeatability of the respective test method are valid.